

Kiario

Safety accessories

The smart flashing-light.


Modern design, attractive materials, luminous efficiency and a special integrated functionality that give periodic maintenance warnings. Thanks to Kiario series of flashing lights not only high safety standards are guaranteed but also other features that make it much more than just a flashing light.




Maximum modularity when mounting.
The radio antenna can be integrated and mounted on either side of the flashing light.



The assistant flashing light.
The KIAROIN and KIARO24IN flashing lights can be set to warn when the system has performed, 5,000, 10,000, 20,000 or 50,000 operations. It is an automatic solution for programming the system's routine maintenance schedule.



Dedicated accessories.
The KIAROS modular, wall-mounting bracket is designed to work in any possible installation scenario. Adjustments: 90°- 180°- 270°.



Advantages of Kiario

The Kiario series flashing lights the result of thoughtful and precise, accurate engineering, are built with extremely high-quality, durable materials. They are designed to meet the application needs of modern, automated installations. Besides the traditional movement-warning function, the KIAROIN and KIARO24IN models, are also equipped with a special "cycle-counter" circuit, which keeps count of a pre-set limit.

This innovative and unique function is extremely useful in programming periodic maintenance jobs.


Limits to use

Model	Lamp (W)	Power supply (V)
KIARON	25	230 A.C. 50/60 Hz
KIAROLXN	6 (XENON)	230 A.C. 50/60 Hz
KIAROIN	25	230 A.C. 50/60 Hz
KIARO24N	25	24 A.C.-D.C.
KIARO24IN	25	24 A.C.-D.C.

● 230V A.C. ● 24V D.C.

Dimensions

Dimensions in millimeters (25,4 mm = 1 in)



Technical features

Type	KIARON	KIAROIN	KIAROLXN	KIARO24N	KIARO24IN
Protection rating	IP54	IP54	IP54	IP54	IP54
Power supply (V)	230 A.C. 50/60 Hz	230 A.C. 50/60 Hz	230 A.C. 50/60 Hz	24 A.C.-D.C.	24 A.C.-D.C.
Dimensions (mm/in)	130x170x76 / 5,11x6,69x2,99	130x170x76 / 5,11x6,69x2,99	130x170x76 / 5,11x6,69x2,99	130x170x76 / 5,11x6,69x2,99	130x170x76 / 5,11x6,69x2,99
Lamp power (W)	25	25	6	25	25
Duty cycle (%)	50	50	50	50	50
Operating temperature (°C/°F)			-20 ÷ +55 / -4 ÷ +131		
Material	ABS - Polycarbonate	ABS - Polycarbonate	ABS - Polycarbonate	ABS - Polycarbonate	ABS - Polycarbonate

120V A.C. - 60 Hz PRODUCTS, PLEASE CHECK OUR PRICE LIST ● 230V A.C. ● 24V A.C. - D.C.



The complete range

230V A.C. flashing lights

- Accessories price list -



001KIARON Flashing light.

001KIAROLXN Flashing light with xenon lamp.

001KIAROIN Flashing light with manoeuvres counter function.



24V A.C.-D.C. flashing lights

001KIARO24N Flashing light.

001KIARO24IN Flashing light with manoeuvres counter function.

Accessories



001KIAROS Wall fixing bracket.